



## PRODUCT SPECIFICATION SHEET

### FULLY INTUMESCENT CABLE TRAY FIRE SLEEVE

#### MODEL REFERENCE

<b>ACT50</b> – To suit 50mm trunking	<b>ACT225</b> – To suit 225mm trunking
<b>ACT75</b> – To suit 75mm trunking	<b>ACT300</b> – To suit 300mm trunking
<b>ACT100</b> – To suit 100mm trunking	<b>ACT450</b> – To suit 450mm trunking
<b>ACT150</b> – To suit 150mm trunking	

- Manufactured from fully intumescent mineral fibre material, which expands to over 3 times its original volume in the event of a fire to seal all air, flame and smoke paths through the opening.
- Meets all the requirements of the UK Building Regulations.
- Tested and approved by Chiltern International Fire to BS 476: Pt.20 & Pt.22: 1987 and the guidelines of EN1366-3 (Fire test assessment No. Chilt/A05153. Duration of effective protection 132 minutes integrity).
- Two hour fire and smoke 'stop' through all common wall constructions and partitions.
- Provide a cold smoke seal as well as thermal and acoustic insulation in their passive state.
- Quickly and easily installed simply by cutting the sleeve to shape, sliding on to the end of the tray, resealing and then sliding into the wall.
- Can easily be retrofitted, without disturbing cables or conduits by slicing and opening the sleeve, fitting it around the tray and resealing with the tape provided.
- Can easily be cut with a standard padsaw.
- Non-toxic and maintenance free.
- Dimensions (mm):

Cat No.	To suit cable tray (mm)	Width (mm)	Height (mm)	Length (mm)
ACT50	50	100	100	150
ACT75	75	125	100	150
ACT100	100	150	100	150
ACT150	150	200	100	150
ACT225	225	275	100	150
ACT300	300	350	100	150
ACT450	450	500	100	150

**Aico Ltd.**,  
Mile End Business Park,  
Maesbury Road, Oswestry, Shropshire SY10 8NN  
Tel: 0870 758 4000 Fax: 0870 758 4012